

"**AIRSTAGE**"™ is a worldwide trademark of FUJITSU GENERAL LIMITED.
FUJITSU brand lineup except for compact cassette (AU7 - 18) was certified by China Compulsory Certification.

All specifications subject to change without prior notice.

Distributed by :

Copyright© 2003-2007 Fujitsu General Limited. All rights reserved.

FUJITSU GENERAL LIMITED
1116, Suenaga, Takatsu-ku, Kawasaki 213-8502, Japan
URL : <http://www.fujitsu-general.com>

2008.04 VB009E/10



AIRSTAGE™

Variable Refrigerant Flow System
Multi Air Conditioning System for Buildings

The Intelligent Choice in Comfort

J SERIES




FUJITSU GENERAL LIMITED

High-performance air conditioning system

The compact VRF System provides economical and comfortable air conditioning for wide range of applications from living space to business space.

Compact VRF System for use in apartments, homes, shops, offices



Apartments

The common areas and individual room spaces in apartment blocks have differing air conditioning needs. What is required is an air conditioning system that provides comfortable conditions and is economical and surroundings conscious.

Homes

Homes need individual air conditioning control for specific rooms that can also be easily switched to standby mode if the occupants have to go out at short notice.



A range which allows an unlimited combination of indoor and outdoor units accord

Outdoor units

Heat Pump	R410A	Cooling Only	R410A
			
AJA54L/AO54U		AJA54J/AO54F	
P4, P5			

Indoor units

Compact Cassette	Cassette	Compact Duct	Low Static Pressure Duct	Duct
	 Slim Type AU20 / AU25 / AU30		 Silent Model ARXB25 / ARXB30	
AU7 / AU9 / AU12 / AU14 / AU18	AU36 / AU45 / AU54	AR7 / AR9 AR12 / AR14 / AR18 / AR22		AR25 / AR30 / AR36 / AR45
P14	P15	P16	P17	P17

Piping material

- Use the correct refrigerant piping and materials for R410A.
- For the pipe wall thickness, see the table below.

Copper pipe outside diameter(Ø)	Ø 6.35	Ø 9.52	Ø 12.70	Ø 15.88	Ø 19.05
Material	Copper JIS H3300 C1220T-O or equivalent ¹⁾				
Copper pipe ²⁾ wall thickness (mm)	0.8	0.8	0.8	1.0	1.2

Note: Always observe and follow the necessary local regulations when installing refrigerant piping.
1) Allowable tensile stress ≥ 33 (N/mm²); 2) Design pressure 4.2MPa.

Tools

- R410A work requires a number of special tools (※ symbol).
Since tools used in R22 work cannot be used, provide the tools separately.

Tool name	Process and application	
Pipe cutter	Pipe cutting	Refrigerant piping work
※ Flaring tool	Pipe flaring work	
※ Torque wrench (1/2, 5/8)	Flare nut connection	
Expander	Expansion at pipe connection	
Pipe bender	Pipe bending work	Air tightness test
Nitrogen gas	Pipe interior oxidation prevention	
Welder	Pipe brazing	Air tightness test ~ Refrigerant additional charging
※ Gauge manifold	Vacuum evacuation and refrigerant charging operation check	
※ Charging hose		Vacuum drying
※ Vacuum pump(with adaptor)		
Electronic scale for refrigerant charging		Refrigerant additional charging
Gas leak tester	Gas leakage test	

Work precautions

Refrigerant check Before work, check the refrigerant used and prepare materials matched to the refrigerant.

Refrigerant piping work Observe the basics (dry, clean) of refrigerant piping and carry out work so that problems will not occur. Moreover, when performing welding work, seal in nitrogen gas and perform work so that an oxide film is not produced.



Leak pressure test Conduct a pressure test sufficiently and make sure there is no refrigerant leakage.

Vacuum drying If the vacuum pump does not have a reverse flow check mechanism, use the pump together with a reverse flow check adapter.

Additional refrigerant Charge only the amount of R410A refrigerant calculated in the additional refrigerant charge calculation. This refrigerant should only be charged in a liquid form.


R410A Work Notes

R410A

The working pressure of R410A is approximately 1.6 times higher than that of R22.
As the oil type is also different, be sure not to mix them.


Refrigerant	R410A	R407C	R22
Oil	POE oil	POE oil	Mineral oil
Pressure ratio	Approx. 1.6	Approx. 1.1	1

Work flow



A compact VRF System that responds to the needs of each building

Backed by advanced air conditioning technology, this compact VRF System was developed to meet six key requirements: high efficiency, economy, comfort, convenience, ease of operation, and easy maintenance. This VRF System delivers a comfortable and economical environment.



and a broad range of other applications



Shops

As shop premises are regularly upgraded and the operating conditions for each can vary so much, large-scale air conditioning management is very difficult. Consequently, a VRF air conditioning system matched to each shop is an ideal solution.

Offices

The spaces within office premises can all have different air conditioning requirements. Energy saving and economic operation are major issues and what is needed is an air conditioning system which can be accurately matched to each space and centrally controlled.



ing to the building and application

Remote controller (Option)		Accessories			
Compact Wall Mounted	Wall Mounted	Group Remote Controller *1	Wired Remote Controller	Simple Remote Controller	Wireless Remote Controller
AS7 / AS9 / AS12 / AS14	AS18 / AS24 / AS30	UTB-YDB / UTB-GDB	UTB-YUB / UTB-GUB / UTB-TUB	UTB-YPB / UTB-GPB / UTB-TPB	UTB-YRA / UTB-GRA / UTB-TRA
P18	P19	P9	P10	P10	P11
					IR Receiver Unit
					(Duct type only)
					P24

*1. Network converter (UTR-YGCA) is required, when installing group remote controller.

High-performance outdoor unit delivering com



R410A


Heat Pump

**AJ*A54LCLR
AO*54UJBM**

Cooling Only

**AJ*A54JCLR
AO*54FJBM**

※ AJ*A: AJYA (FUJITSU) AJ*A: AJGA (GENERAL)
AO*: AO (FUJITSU) AO*: AOG (GENERAL)



Powerful operation with low electricity consumption

- Excellent COPs are attainable as shown in the table below.

Cooling COP	3.20*
Heating COP	3.40*


* "COP" is the coefficient of performance
(= capacity (kW) ÷ input power (kW)).
※ COP values are based on our own testing method.

- Uses a high-performance DC inverter scroll compressor with variable capacity according to the load during cooling and heating.




High-capacity connection possible

- One outdoor unit can connect to up to 8 indoor units.
- Connectable capacity is 150% of the outdoor unit rating and can cope with a range of operating modes.



Operating outside air temperature range

- Outdoor unit operates over an ambient temperature range of -5°C to 43°C for cooling and -20°C to 21°C for heating.




Optional Parts

EV kit

**UTR-EV2AXL
UTR-EV3XL**

- EV kit is available for installation as necessary.


Model code < 30 : UTR-EV2AXL
Model code ≥ 30 : UTR-EV3XL



Separation tube

UTR-BP054X / UTR-BP54U

- Separation tubes are available for installation as necessary.



Grille kit

**UTG-UDYD-W
UTG-UDGD-W**

- Grille for compact cassette type indoor unit.



Header

UTR-HD546U

- Headers are available for installation as necessary.



Remote sensor unit

UTD-RS100

- Thermo sensor for sensing the temperature of an arbitrary place in the room



Drain pump unit

UTZ-PX1BBA

- For compact duct type



Flange (Square)

UTD-SF045T

- For duct type
205 x 1,063, L=40 (mm)



Flange (Round)

UTD-RF204


- For duct type
Ø195 (Ø205), L=85 (mm)



Air clean filter

UTR-FA08

- For wall mounted type
- Air clean filter assembly for initial setting.



Air clean filter

UTR-FB03


- Replacement filter for UTR-FA08



Long-life filter

UTD-LF270

- For duct type



Accessories

Wireless remote controller

- Supplied with each indoor unit



IR receiver unit

- IR receiver unit is connected for each duct type indoor unit.



Optional Parts

Group remote controller

UTB-YDB / UTB-GDB


- Up to 8 indoor units can be controlled by a single controller.
- When air conditioner ON/OFF and temperature setting are preset automatically by using a weekly timer, operation can be started and stopped automatically.



Wired remote controller

UTB-YUB / UTB-GUB UTB-TUB

- Wired remote controller capable of controlling each indoor unit individually.
- Can be used together with wireless remote controller.



Simple remote controller

UTB-YRA / UTB-GRA UTB-TRA


- Concentrates on basic operations such as On/Off, Fan Control and Temperature Setting.



Network converter

UTR-YGCA

- Network converter is required to connect Group Remote Controller to an VRF system.



Simple remote controller

UTB-YPB / UTB-GPB UTB-TPB


- Concentrates on basic operations such as On/Off, Fan Control, Master Control and Temperature Setting.



External switch controller

UTR-YESA

- Switching of the air conditioner can be controlled by connecting other sensor switches.




fort and economy


Lightweight and compact design

- Small, compact casing can be easily concealed.

Dimensions H900 x W900 x D370mm




(Unit: mm)



The low overall height allows the unit to be neatly positioned beneath a window.

Low height and lightweight design



120kg

Conventional type
15.2kW single type

97kg


AIRSTAGE J
15.2kW VRF

Noise reduction

- Newly designed larger fan and double casing bell mouth construction reduce noise emissions.

Large fan

Low-speed design suppresses noise by using a larger fan.




Double casing bell mouth

Double casing bell mouth helps to reduce noise.

Blue fin heat exchanger mounted

- Corrosion-resistance of the heat exchanger even in coastal areas has been improved by blue fin treatment of the outdoor unit heat exchanger.

Blue fin heat exchanger



*Cobalt blue protection (Blue Fin) is a standard specification of AJ*A54LCLR, AJ*A54JCLR.


Compact VRF System allows design flexib

Flexible design


Superior design flexibility allows individual air conditioning of multiple rooms.

System that allows individual air conditioning of multiple rooms


Homes



Shops




Offices




Piping connection examples

Separation tube system




Separation tube + header system



Easier outdoor unit installation

- Discreet installation



Height	900
Width	900
Depth	370

Unit: mm

The compact dimensions allow the outdoor unit to be installed below a window.

Large capacity connectable


- Up to 8 indoor units can be connected to 1 outdoor unit. Furthermore, the indoor unit connection capacity can be up to 150% of the outdoor unit rating. This increases design flexibility.

Max 8
Indoor units
connectable

150%
Connectable
capacity

Long piping length

- The maximum piping length is 70m, and can cope with a wide range of applications from homes to offices.



All indoor units are supplied with a remote controller


- All indoor units come with a wireless remote controller.

Note: IR receiver unit is available for duct type indoor unit.

Indoor unit Compact Duct (Unit : mm)

Models: AR7 / AR9 / AR12 / AR14 / AR18 / AR22

*Service accessibility must be allowed for when installing the product.
Please consult the installation manual for the necessary service access size.




- Refrigerant piping flare connection (Liquid)
- Refrigerant piping flare connection (Gas)
- Drain piping connection (Drain pipe : I.D. Ø21.5 O.D. Ø26.0)

Indoor unit Low Static Pressure Duct / Duct (Unit : mm)

Models: ARXB25 / ARXB30
AR25 / AR30 / AR36 / AR45


*Service accessibility must be allowed for when installing the product.
Please consult the installation manual for the necessary service access size.



- Refrigerant piping flare connection (Liquid)
- Refrigerant piping flare connection (Gas)
- Drain piping connection (Drain pipe : I.D. Ø35.7 O.D. Ø38.1)

Indoor unit Compact Wall Mounted (Unit : mm)


Models: AS7 / AS9 / AS12 / AS14



- Refrigerant piping flare connection (Liquid)
- Refrigerant piping flare connection (Gas)
- Drain piping connection (Drain hose : I.D. Ø12 O.D. Ø16.2-17 L 620)




Indoor unit Wall Mounted (Unit : mm)

Models: AS18 / AS24 / AS30



- Refrigerant piping flare connection (Liquid)
- Refrigerant piping flare connection (Gas)
- Drain piping connection (Drain hose : I.D. Ø17 O.D. Ø24 L 670)

Dimensions




ility and efficient operation

Easy installation Quick and easy to install.

Easy to understand piping and wiring installation


- The wiring work is simple in the connection wiring system one by one.
- The dedicated communication line is unnecessary.
- The electrical work is simple because of single-phase power supply.

System diagram




System addressing

- During installation work, system addressing can be performed using the wireless remote controller, thus eliminating manual switch setting.



Easier installation of the outdoor unit

- Compact size and lightweight




Weight

97kg


The outdoor units is light and compact and easy to handle during installation.

Control system that always provides a pleasant air conditioned environment

Five types of controllers are available to meet the varied needs of the building and the user. Tighter control over the air conditioned environment can be achieved by combining group remote controller which can operate all the indoor units at the same time, a wired remote controller with a weekly or daily schedule, a wireless remote controller and a simple remote controller.



System diagram



Indoor unit		Compact Duct						Low Static Pressure Duct		Duct					
Model code		AR7	AR9	AR12	AR14	AR18	AR22	ARXB25	ARXB30	AR25	AR30	AR36	AR45		
Model name		ARXA07 LALR	ARXA09 LALR	ARXA12 LALR	ARXA14 LALR	ARXA18 LBLR	ARXA22 LBLR	ARXB25 LATR	ARXB30 LATR	ARY25 UFAAR	ARY30 UFAAR	ARY36 UFAAR	ARY45 UFAAR		
Power source		220-240V, 50Hz													
Cooling capacity	kW	2.15	2.80	3.50	4.00	5.30	6.00	7.05	8.80	7.05	8.80	10.5	12.7		
	BTU/h	7,300	9,600	11,900	13,700	18,100	21,100	24,100	30,000	24,100	30,000	36,000	43,500		
Heating capacity	kW	2.45	3.10	4.10	4.80	5.60	6.30	7.85	9.10	7.85	9.10	10.7	13.7		
	BTU/h	8,400	10,600	14,000	16,400	19,100	21,500	26,800	31,000	26,800	31,000	36,500	47,000		
Input power	W	32		49		103		155		155		315			
Current	A	0.20		0.24		0.45		0.70		0.68		1.44			
Maximum current		0.24		0.29		0.54		0.40		0.84		1.84			
Heat exchanger		Plate fin coil													
Air circulation	High	420		620		950		890		1,340		1,200		2,200	
	Med	390		550		790		780		1,090		1,100		2,000	
	Low	360		470		620		670		970		1,000		1,800	
Recommend static pressure		Pa	0 to 40						0 to 80		30 to 160		30 to 180		
Fan type x number		Sirocco x 1			Sirocco x 2										
Fan motor output		W	10		14		52		36		47		77		275
Noise level (sound pressure)	High	34		33		40		42		33		44		49	
	Med	32		29		35		38		29		42		47	
	Low	31		27		30		34		26		40		45	
Air filter		PP monofilament net (Antibacterial / Deodorization)						Filter : UTD-LF270 (Option) PP honeycomb net, Fungicide Type							
Dimensions (H x W x D)	Net	mm	217 x 663 x 595		217 x 953 x 595				270 x 1,210 x 700						
	Gross		324 x 785 x 686		324 x 1,075 x 686				300 x 1,320 x 790						
Weight	Net	kg	18		25		43				45				
	Gross		22		29		53				55				
Pipe size	Diameter	mm	Ø 6.35					Ø 6.35	Ø 9.52	Ø 6.35	Ø 9.52				
	Gas		Ø 9.52		Ø 12.70		Ø 15.88					Ø 19.05			
Connection method		Flare													
Drain pipe material	Dia. (mm)	ABS/Outer diameter 26mm / Inner diameter 21.5mm						Steel/Outer diameter 38.1mm / Inner diameter 35.7mm							

Note: Specifications are based on the following conditions.





Cooling: Indoor temperature 27°CDB/19°CWB, and outdoor temperature 35°CDB/24°CWB).
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature 7°CDB/6°CWB.
Standard static pressure: 0Pa (AR7 to AR22, ARXB25, ARXB30), 100Pa (AR25 to AR45).
Voltage: 230 [V]

AS* : AS (FUJITSU), ASG (GENERAL)

Indoor unit			Compact Wall Mounted				Wall Mounted		
Model code			AS7	AS9	AS12	AS14	AS18	AS24	AS30
Model name			AS*7 UFADR	AS*9 UFADR	AS*12 UFADR	AS*14 UFADR	AS*18 UFAJR	AS*24 UFAJR	AS*30 UFAJR
Power source			220-240V, 50Hz						
Cooling capacity	kW	2.15	2.80	3.50	3.80	5.40	6.90	8.00	
	BTU/h	7,400	9,600	11,900	13,000	18,400	23,600	27,300	
Heating capacity	kW	2.45	3.10	4.10	4.50	5.60	7.80	8.80	
	BTU/h	8,400	10,600	14,000	15,400	19,100	26,600	30,000	
Input power	W	26	33	40		38	50	60	
Current	A	0.15	0.17	0.21		0.18	0.24	0.28	
Maximum current		0.18	0.21	0.24		0.22	0.29	0.34	
Heat exchanger			Plate fin coil						
Air circulation	High	m³ / h	410	500	540		840	950	1,050
	Med		370	450	510		700	800	940
	Low		350	410	480		600	670	780
Fan type x number			Cross flow x 1						
Fan motor output			W	13			38		
Noise level (sound pressure)	High	dB (A)	30	36	39		42	45	48
	Med		27	33	37		39	41	45
	Low		26	30	34		35	37	41
Air filter			PP honeycomb (Antibacterial and Mold proofing)				PP monofilament net (Deodorization, Anti-mold)		
Casing color			White				White		
Dimensions (H x W x D)	Net	mm	257 x 808 x 187				320 x 1,120 x 220		
	Gross		270 x 850 x 310				348 x 1,240 x 427		
Weight	Net	kg	8				16		
	Gross		10				22		
Pipe	Diameter	Liquid	mm	Ø 6.35				Ø 9.52	
		Gas		Ø 9.52		Ø 12.70		Ø 15.88	
	Connection method			Flare					
Drain pipe material		Diameter (mm)	With 620mm drain hose, PVC / Outer diameter 16.2-17mm / Inner diameter 12mm				With 670mm drain hose, PVC / Outer diameter 24mm / Inner diameter 17mm		

Note: Specifications are based on the following conditions.

Cooling: Indoor temperature 27°CDB/19°CWB, and outdoor temperature 35°CDB/24°CWB).
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature 7°CDB/6°CWB.
Voltage: 230 [V]




A controller can be chosen according to user comfortable, easily adjustable air flow

Wired Remote Controller

UTB-YUB / UTB-GUB / UTB-TUB [Option]


Weekly timer and timer function are easily operated.

Dimensions (H x W x D) 120 x 120 x 17




Powerful features and compact size

Wired remote controller, Weekly timer and Setback timer functions are combined in one compact unit.




Accurate and Comfortable

Indoor temperature can be detected accurately because a thermo sensor has been added in the body of the wired remote controller. The detecting point in the room can be freely changed with the new type wired remote controller (thermo sensor added) and remote sensor (Option).



Control button for changing the thermo sensor




Simple Remote Controller

UTB-YPB / UTB-GPB / UTB-TPB [Option]

UTB-YRA / UTB-GRA / UTB-TRA [Option]

Simple remote controller concentrating on basic operations.

Dimensions (H x W x D mm) 120 x 75 x 14



Simple operation

- A large Start/Stop button is provided in the centre of the remote controller unit for easy operation.
- The backlight is lit during button operations, and for 10 seconds longer in the operation mode and 5 seconds longer in the stop mode.



UTB-YPB / UTB-GPB / UTB-TPB

UTB-YRA / UTB-GRA / UTB-TRA Without master control

Functions	Model	UTB-YPB UTB-GPB UTB-TPB	UTB-YRA UTB-GRA UTB-TRA
Operation			
On/Off		●	●
Fan control		●	●
Master control		●	—
Temp. setting		●	●

Wall Mounted

AS*18UFAJR AS*24UFAJR AS*30UFAJR




Features


Pleasant multi-air flow

Effective air flow within a room is achieved by the unique operation of the power diffuser. The angle of the louvre can be adjusted in six steps to give draught-free air flow.

Wide air flow realized by unique operation of the power diffuser



Symmetrical design



Other functions

Other features include the functions of the existing wall mounted type.


- 2-way draining route
- Double auto swing

Optional parts

Air clean filter (UTR-FA08)

Easy installation

Larger space at base of housing means an extra 15% of piping space.



Attractive wall-mounted unit that delivers a needs

Compact Wall Mounted

AS*7UFADR AS*9UFADR AS*12UFADR AS*14UFADR



Wireless Remote Controller

Features

*AS7/AS9/AS12/AS14 are only available for wireless remote controller.

Symmetrical design

Symmetrical, clean design that suits all interiors.

Compact size

Powerful output in spite of small size

Though the indoor unit is compact, it features a large, high pressure cross fan (90mm diameter) in a centre mounted configuration and a Lambda type heat exchanger to provide plenty of power.

Height	257
Width	808
Depth	187

Unit: mm




Low noise

Fan speed	dB (A)
HIGH	30
LOW	26

*AS7 model data


Auto swing louvre

The Auto Swing Louvre function ensures that the air direction corresponds to the mode selected.





Washable open panel

Cleaning the washable panel removes mould and dust.



A regular wipe with a dry cloth keeps the casing clean.




Since the panel is removed and easily washed, it is always clean. Filter cleaning is also simple.

Wireless Remote Controller [Accessory]

Four kinds of timers. Easy operation.

- Wireless remote controller is an accessory of all indoor units.
- An IR Receiver Unit necessary for operation by accessory wireless remote controller is connected to Duct type indoor unit.

Dimensions (H x W x D mm) 158 x 56 x 20



Built-in daily timer


Select from 4 different timer programs : On / Off / Program / Sleep

*1: Program timer / The program timer operates the ON and OFF timer once within a 24 hour period.

*2: Sleep timer / The sleep timer function automatically corrects the set temperature according to the time setting to prevent excessive cooling or heating during sleep hours.


Cooling operation / dry operation

When the sleep timer is set, the set temperature automatically rises 1°C every hour. The set temperature can rise up to a maximum of 2°C.




Heating operation


When the sleep timer is set, the set temperature automatically drops 1°C every 30 minutes. The set temperature can drop to a maximum of 4°C.



Simple operation



• Code selector switch prevents units from being wrongly switched. (Up to 4 codes can be set.)



External Switch Controller



UTR-YESA [Option]

- On/Off, Temperature, Fan control, and Master control can be switched in combination equipped with the Card-key switch or sensor switch.
 - Switching of the air conditioner can be controlled by connecting other sensor switches.
- *Card-key and other sensor switches are available as field supplied parts.

Dimensions (H x W x D mm) 120 x 75 x 30

Installation example

- Auto mode operation, which switches the cooling and the heating auto-matically, is enabled by using the sensor switch and external switch controller. In that case, all indoor units run in the same operation mode.



Select to match the capacity and type of the room very low ceilings

Indoor unit line up 7 types 30 models, ranging from 2.15kW to 14.10kW.

Capacity range (kW)▶	2.15	2.8	3.6	4.0	5.3	5.7
▼ Type Model code▶	7	9	12	14	18	20
Compact Cassette P14	 AU7UFAAR	 AU9UFAAR	 AU12UFAAR	 AU14UFAAR	 AU18UFAAR	
Cassette P15						 AU*20UFARR Slim Type
Compact Duct P16	 ARXA07LALR	 ARXA09LALR	 ARXA12LALR	 ARXA14LALR	 ARXA18LALR	
Low Static Pressure Duct P17 Silent Model						
Duct P17						
Compact Wall Mounted P18	 AS*7UFADR	 AS*9UFADR	 AS*12UFADR	 AS*14UFADR		
Wall Mounted P19					 AS*18UFAJR	

•AU*: AUY(FUJITSU), AUG(GENERAL) •AS*: ASY(FUJITSU), ASG(GENERAL)

Low Static Pressure Duct Silent Model

ARXB25LATR ARXB30LATR

Duct

AR25UFAAR AR30UFAAR
AR36UFAAR AR45UFAAR




*Wireless remote controller and IR receiver unit is supplied with all duct type indoor units.

Features

Low static pressure duct type


■ Optimum model for hotels or bedrooms



An ultra low-noise model that achieves a quiet interior. Perfect for hotels or bedrooms with limited air duct installation space.


■ Installation styles

Direct air flow installation can be performed. Air intake system can also be chosen.




Savings in space and easy installation


Slim compact design allows for easy installation in narrow ceiling space.



Suspended Installation




Direct Installation




Duct type

■ Powerful model with a flexible design


With a powerful motor, appropriate for a wide range of static pressure. Flexible air duct installation is possible in a large space such as an office.



■ Installation styles



Two-direction drain piping




Optional parts

Flange (square)	UTD-SF045T
Flange (round)	UTD-RF204
Long-life filter	UTD-LF270
Remote sensor unit	UTD-RS100

Ultra-slim duct air conditioner for use with

Compact Duct

ARXA07LALR ARXA09LALR ARXA12LALR
ARXA14LALR ARXA18LALR ARXA22LALR



*Wireless remote controller and IR receiver unit is supplied with all duct type indoor units.

Features

Compact and space-saving design

Ultra-slim unit simplifies installation.




Low noise level

These compact duct type units are extremely quiet.

Model	7	9	12	14	18	22
Static pressure (standard/max) Pa	0 / 40					
Air flow volume (high/low) m³/h	420/360	620/470	950/620	890/670		
Noise level (Low speed) dB(A)	31	27	30	34		

Easy installation (Universal type)

Slim and compact dimensions allow for ceiling installation or floor standing.



Perfectly housed in ceiling space.

Perfectly housed in the space below a window.


Installation example




Optional parts

Remote sensor unit UTD-RS100
Drain pump unit UTZ-PX1BBA

Two-direction drain piping



Filter (Accessory)



Others

- Air intake from rear or bottom side
- Two direction drain piping

Accessories

	6.0	6.9	7.05	8.8	10.5	12.7	14.1	Wireless Remote Controller	IR Receiver Unit
	22	24	25	30	36	45	54		
									
									
									
									
									
									
									
									

Slim and compact cassette, designed for limited ceiling space

Compact Cassette


AU7UFAAR AU9UFAAR AU12UFAAR
AU14UFAAR AU18UFAAR



Features


Compact size

Compact grille fits European ceiling panel (600mm x 600 mm).




Easy maintenance

Placing all the electrical components inside the unit ensures easy maintenance.




Condensate pump lifts to 400mm




Comfortable air flow

4-step swing: Auto air flow direction and auto swing




2-4 way air flow system:

Select 2-way, 3-way, or 4-way air flow to suit your needs.




Extremely quiet

Large air flow at reduced noise output achieved by incorporating a large diameter variable pitch turbo fan.



Draught prevention

The angle of the flap can be changed during installation, thereby preventing uncomfortable draughts.



Optional parts

Grille kit UTG-UDYD-W, UTG-UDGD-W

Cassette Slim Type

AU*20UFARR AU*25UFARR AU*30UFARR

Cassette

AU*36UFASR AU*45UFASR
AU*54UFASR




Features

Flexible installation

Compact body ensures space saving installation. A slender fit option is available where ceiling void space is limited.

	Standard setting	Slender setting
	Ha	Hb
AU20 / AU25 / AU30	235	200
AU36 / AU45 / AU54	285	250

Easy maintenance




Condensate pump lifts to 800mm



Comfortable air flow


4-step swing

Auto air flow direction and auto swing



2~4 way air flow system

Select 2-way, 3-way or 4-way air flow to suit your needs.




Wide air flow


Unit louvre distributes the outlet air flow further in the horizontal direction.

Duct connection hole opening

Fresh air can be introduced through this opening.



Conditioned air can be distributed by means of a distribution duct.



Improved noise level and air distribution

Noise output has been dramatically lowered.

- Improved turbo fan shape (aerodynamic design)
- Expanded air distribution
- Low internal resistance
- Moulded fan motor

Draught prevention

The angle of the flap can be changed during installation, thereby preventing uncomfortable draughts.

