

Optional Parts

Connection Units

Separation Tube

UTR-BP090X or UTP-AX090A 	UTR-BP180X or UTP-AX180A 	UTR-BP567X or UTP-AX567A
UTP-BX090A 	UTP-BX180A 	UTP-BX567A

Header

UTR-H0906L UTR-H1806L 	UTR-H0908L UTR-H1808L 	UTP-DX567A
UTP-J0906A UTP-J1806A 	UTP-J0908A UTP-J1808A 	

EV Kit

Model code ≤ 09 : UTR-EV09XB Model code ≥ 12 : UTR-EV14XB
For Compact Wall Mounted type

RB Unit

UTP-RX01AH UTP-RX01BH UTP-RX01CH 	UTP-RX04BH
Single type	Multi type

Specifications

Separation Tube

Model name	UTR-BP090X or UTP-AX090A	UTR-BP180X or UTP-AX180A	UTR-BP567X or UTP-AX567A
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	56.1 or more
Model name	UTP-BX090A	UTP-BX180A	UTP-BX567A
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	56.1 or more

Header

Model name	3-6 Branches	UTR-H0906L	UTR-H1806L
Model name	3-8 Branches	UTR-H0908L	UTR-H1808L
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0
Model name	3-6 Branches	UTP-J0906A	UTP-J1806A
Model name	3-8 Branches	UTP-J0908A	UTP-J1808A
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0

Outdoor unit Branch kit

Model name	UTP-DX567A	
Number of Outdoor unit	2 outdoor units	1
	3 outdoor units	2

EV Kit

Model name	UTR-EV09XB	UTR-EV14XB
Application Model	AS*E07GACH AS*E09GACH	AS*E12GACH AS*E14GACH

AS* : ASY(FUJITSU), ASH(GENERAL)

RB Unit

Type		Single type			Multi type
Model name		UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX04BH
Power source		Single phase 230V, 50Hz			
Input power	W	17	24	31	96
Number of branches		1	1	1	4
Maximum capacity of connectable indoor units(Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 56.0 *1
Maximum capacity of connectable indoor units per branch(Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 18.0
Maximum number of connectable indoor units per branch		3	8	8	8
Dimensions (H×W×D)	mm	198 X 298 X 268			260 X 658 X 428

*1: In case of two RB units connected in series (total 8-branches), maximum capacity of connectable indoor units is up to 56.0kW.